

FOBRO Mobil tool-carrier D60 4X2 / 4X4



The FOBRO Mobil D60 is the logical evolution from the previous FOBRO Mobil B23. Main characteristics, especially the overhead frame is kept and improved with the possibility to extend its wheel base up to 75cm (30"). Excellent access to the mid mount/central three point hitch together with its maximum visibility ensures the best performance of precision tasks like: seeding (even on ridges), hoeing, inter row tilling, fertilizing, spraying, bed trimming and many more delicate maintenance jobs. Due to the three mounting areas, front, central and rear, multi-tasking becomes affordable and efficient.

Bärtschi-FOBRO AG
 Bernstrasse 26 | CH-6152 Hüswil/Schweiz
 Tel: ++41 (0) 41 98 98 111 | Fax: ++41 (0) 41 98 98 121
www.fobro.com | e-mail: info@fobro.com

FOBRO Mobil tool-carrier D60 4X2 standard:

Motor	60 HP PERKINS 4 Cylinders soundproof
Hydrostatic transmission	2 range SAUER pump, POCLAIN rear wheel engines, twin lock anti sliding.
Infinitely variable speed	1. range 0-12Km/h (7,5mph), 2. range 0-25Km/h (15,5mph)
Tires	Front 7.5 R18, rear 9.5 R32
Variable track width	From 1500 to 2100mm (59"-82"), mechanically adjustable
Wheel base	From 2570 to 3320mm (101" to 130") mechanically adjustable
Ground clearance	Net 750-800mm (29,5"-31,5")
Weight	2400Kg (5290lbs)
Central 3-point hitch	Cat. 2, max. 1000Kg (2200lbs), one double acting hydraulic outlet
Rear 3-point hitch	Cat. 2, max 1500kg (3300lbs) two double acting hydraulic outlets

Options:

Four wheel drive, (4X4)	Four wheel hydrostatic drive with "TWIN LOCK" anti sliding system
Central PTO	Hydraulic central PTO 540 or 750 rpm
Rear PTO	Hydraulic rear PTO 540 rpm
Front 3-point hitch	Cat. 2, max. 400Kg (880lbs)
Comfort Cabin	Pressurized, active carbon filtered and air conditioned cabin
Extra ground clearance	Net 950-1000mm (37,5" to 39,5")
And many other options	Please ask and let us know about your special requirement

Bärtschi-FOBRO



FOBRO Mobil tool carrier D60 4X2 / 4X4

Standard equipment

Your advantage

Hydraulic drive with two infinitely variable speed ranges

The work and travel range from zero to maximum speed keeps the motor always at the desired rpm range and at its optimum torque. This allows keeping implement speed and ground speed as well as motor performance in the perfect and safe balance.

Quietized Motor

Sound and thermal isolation add to the driver's comfort and support excellent job performance. Engine maintenance is easy as the complete isolation hood can be taken off.

Adjustable, heavy central beam

The over the top central beam allows for adjusting the wheel base to make room for nearly any existing implements. Due to the height of the beam standard three point machines will fit easily mid mounted with no alterations.

Adjustable wheel track

Future possible plant pattern changes are possible without extra investments.

Electronic JOYSTICK control lever for hydraulic operations

With one JOYSTICK-lever it is possible to control all functions like forward and reversing, three point hitch front, central and rear as well as the auxiliary hydraulic double acting control valves.

Additional control buttons for central and rear hydraulic

When mounting the implements to the central and/or rear three point, this offers more comfort more security for the operator.

Optional equipment

Your advantage

Four wheel drive with TWIN LOCK anti sliding system

Even while driving a curve, maximum traction on the four wheels is supplied. This reduces soil compaction and damage. Especially in rough terrain the tractor will stay stable and is much easier to steer as conventional differential driven vehicles.

Front three point hitch

Ideal for fertilizing up front and following incorporation with any hoeing tool.

Central and or rear PTO

Any tiller, sprayer, sickle bar or other power driven machines can be empowered in the middle or rear three point hitch area.

Comfort cabin

With this comfort the use of the FOBRO Mobile is even more enjoyable without heat, cold or dust.



Bärtschi-FOBRO AG
Bernstrasse 26 | CH-6152 Hüswil/Schweiz
Tel: ++41 (0) 41 98 98 111 | Fax: ++41 (0) 41 98 98 121
www.fobro.com | e-mail: info@fobro.com

Bärtschi-FOBRO

06-07 We reserve the right to make technical product improvements.