

# FOBRO Start Bed Lifter / Shaker



FOBRO Start the machine for all uses where high clearance is not criteria number one. Build to lift bareroot liners such as Strawberry, Perennials, Ornamental- and Forestry Seedlings, Herbaceous and Medical Plants, various Vegetables and many more.

The functioning (identical to the one used on larger models) proved for over 30 years and still used daily in thousands of nurseries worldwide.

## Technical Information

FOBRO Start	Type 0800	Type 1350	Type 1500
Bed Lifter/Shaker			
Working width	80 cm / 32"	135 cm / 53"	150 cm / 59"
Working depth	25 cm / 10"	25 cm / 10"	25 cm / 10"
Wheel track 1	104 cm / 41"	159 cm / 63"	174 cm / 69"
Wheel track 2	119 cm / 47"	174 cm / 69"	
Overall width	122 cm / 48"	177 cm / 70"	192 cm / 76"
Overall length	175 cm / 69"	175 cm / 69"	175 cm / 69"
Overall height	127 cm / 50"	127 cm / 50"	127 cm / 50"
Weight	490 kg 1080 lbs	510 kg 1125 lbs	520 kg 1146 lbs
Required hp (min.)		35 hp / PS	40 hp / PS
P.T.O. shaft		540 rpm	540 rpm
		Working rpm max. 330 rpm	

**Bärtschi-FOBRO**



# FOBRO Start Bed Lifter / Shaker

## Standard equipment

In driving direction oscillating undercutter blade with lifting / shaking bars

Second rear shaker right after the first lifting / shaking bars

Adjustable working angle of the rear shaker

Four individually adjustable wheels through cranks, no tools needed

All new ingenious drive system

Replaceable wearblades

All pivot points above ground in gab free rubber metal bushings

## Optional equipment

Quick coupling three point hitch, triangle system ACCORD

Counter discs to mount vertically left and right in front of the undercutting blade

## Your advantage

Less traction or horsepower needed, the blade cuts itself through the ground. The soil is not scooped up and compacted as with rigid blades. Therefore you harvest more of the roots and that means higher survival rate.

This ensures a gentle and soil free lifting of the plants.

In wet and muddy conditions, this increases fracturing of heavy / clody soils.

Provides good stability. The machine keeps its precise working depth.

The ingenious design of the drive ensures a very quiet operation. Without a traditional eccentric drive system and gearboxes there are less strokes to the tractor or the P.T.O. shaft. Less wear and tear.

Wear blade made of very high wear resistant material and the blade fixture in high carbon steel.

Gab free means frame destroying vibrations are eliminated. No pivot points in the ground and 100% maintenance free rubber metal bushings makes this machine a very low maintenance tool. Lubrication service reduced to a minimum.

## Your advantage

If you work with the quick coupling system ACCORD you can order the FOBRO Start with the integrated triangle or add it on any time in the future.

Mainly when digging strawberry liners, this coulter cut the runners in front of the blade to prevent plugging up.

Bärtschi-FOBRO AG

Bernstrasse 26 | P.O. Box 1 | CH-6152 Hüswil/Switzerland

Telephone: --41 (0) 41 988 21 21 | Fax: --41 (0) 41 988 22 86

www.fobro.com | e-mail: info@fobro.com

98-09-001 We reserve the right to make technical corrections and product improvements anytime.

**Bärtschi-FOBRO**

